

ULTIMO – options:

High Security External Manual Override



If the only access into the garage is via the rolling garage door, a lockable, hand operated override can be installed.

This external hand operated override allows the door to be opened in the event of a local mains failure.



A battery backup can be supplied as an alternative to the hand operated manual override.

The battery backup is especially useful in rural areas where mains failures may be more frequent or for use by elderly or disabled home owners.



Vision Panels



Full width, heavy duty, extruded aluminium sections with polycarbonate glazing, can be included in your rolling door to increase the light level within the garage during daylight hours. The polycarbonate glazing can be supplied with a frosted finish if security is an issue.



If additional 'i Like' remote controls are required, it is more cost effective to buy them with the door to eliminate the need for an engineer to code one to your receiver at a later date.

A wireless paddle switch can also be installed to allow the door to be operated from a remote, indoor location which can be up to 30 metres from the garage door.



Additional Remote Controls and Switches

Colour Coordination

All doors can be supplied with colour matched guides, head plates and covers so that all of the door's structure is the same colour.

Additional Information

All ULTIMO rolling garage doors can be installed to the internal face of the brickwork reveals, between walls or on the outside face of the brickwork.

As standard, all guide channels, head plates and covers will be supplied in a choice of White or Brown.

All doors will be measured prior to production to ensure that you are supplied with the door and fixing arrangement to exactly suit your requirements.

The bottom rail and safety seal on all doors will project below the base of the head plate by 85 mm.

The colourfast paint finish requires an occasional wash with a damp cloth and soapy water.

The finish on the curtain within the guide channel area may wear after a period of time.

The nylon locking straps supplied with each door are fitted within locking rings which are covered in felt to reduce markings that may occur on the internal face of the door at high level

the ULTIMO insulated rolling garage door



REGIONAL DOORS & SHUTTERS LTD

1 Donkin Road · Armstrong Industrial Estate · Washington · Tyne & Wear NE37 1PF

Telephone: 0191 417 8866 · Facsimile: 0191 417 8889 · eMail: paul@rdands.co.uk

Manufacturing and Delivering Quality!



The ULTIMO insulated rolling garage door is the ultimate in superior quality and design. Beware of more costly imitations and buy in confidence direct from the manufacturer.

5 Year Motor Warranty · 2 Year Guarantee on all manufactured parts · 10 Year Colour Fast on all door colours

Accept nothing less!

The ULTIMO is manufactured from top quality, European made, 77 mm x 18 mm, twin-walled aluminium sections each of which is filled with thermal foam insulation. The rolling doors can be individually designed to meet both site specific requirements and your personal needs.

All ULTIMO garage doors are electronically operated and include an internal light as standard. A manual override facility is also included to allow the door to be opened and closed from the inside of the garage in the event of a power failure.

Operation of the door is via dedicated, high security, 'rolling code', remote control handsets. The system works on the new EC licensed frequency of 868.35 MHz and provides more security than older 433 MHz systems.

The ULTIMO – features at a glance:

- All ULTIMO doors are built in our Washington, UK factory and can therefore be supplied extremely quickly.
- The insulated twin-wall structure gives much greater rigidity and strength than conventional single skin garage doors. It also provides a high level of both thermal and sound insulation.
- Two polyester side guide channel options are available for the ULTIMO door to run within. Both channels are supplied with internal brush seals to stop draughts, reduce wear and ensure quiet, smooth operation.
- The ULTIMO curtain is supplied in a pre-coated aluminium finish which is available in a wide range of colours and texture finishes to provide the appearance required.
- The bottom edge of all ULTIMO garage doors is finished with a rigid, heavy duty extruded aluminium profile which carries a flexible rubber draught excluding seal along a level threshold.
- Heavy duty locking straps ensure that an ULTIMO door is rigidly locked when fully closed. The door's locking rings are provided with protective straps to minimise any marking on the top section of the curtain.
- Two hand transmitters are supplied as standard with each ULTIMO door.
- The ULTIMO motor is always supplied with an internal manual override facility for use in the event of a mains supply failure. A secure external override option is also available (see optional extras).
- All ULTIMO doors are supplied with a wireless safety edge which stops the travel of the door upon detection of an obstruction.

Colour and Textured Options

Standard Colours					
	Bright White 01	Brown 02			
Optional Colours					
	Black 10	Aluminium 03	Beige 05	Blue 66	Red 52
					
	Grey 04	Dark Grey 67	Light Green 58	Dark Green 55	Ivory 26
Textured Finishes					
	Mahogany 15	Rosewood 12	Dark Oak 19	Golden Oak 18	

The textured wood finishes are a match for many uPVC window frames, they are very hard wearing and carry a limited ten year warranty. The colours shown here are for guidance only. If colour matching is critical please refer to a product sample swatch.

ULTIMO – the components:



Remote Control

The high security 868.35 MHz 'rolling code' remote control incorporates narrow band radio receiver technology to prevent interference from any local radio signals such as wireless alarms and TETRA emergency communications etc. All units incorporate a built-on light as standard.

Wireless Safety Edge

The wireless safety edge cover the whole width of the bottom edge of the door. It is pressure sensitive and triggers the system to stop and return to the fully open position upon detection of an obstruction.



Aluminium Side Guide



Heavy duty aluminium side guides are supplied with a depth and profile to suit the ULTIMO door's size and the available space. All guides are supplied finished in white or brown with noise reducing brush seals, to ensure smooth operation. Side-guides are available in other colours to special order.

Heavy Duty Hollow Section and Safety Seal

The bottom edge of the ULTIMO door consists of a heavy duty, extruded, aluminium section which carries a rubber seal. The flexible rubber seal, which extends across the total width of the door, not only provides an effective barrier against the wind but it also includes the sensing channel for the wireless, optical safety system.



Security Locking



When the ULTIMO door is fully closed it is locked in place by heavy duty nylon locking straps which prevent the door being forced open.

Internal Manual Override

All ULTIMO doors are supplied with an internal, emergency manual override facility for use in the event of a mains supply failure. An external manual override can be supplied as an optional extra.

